ILLINOIS COMMERCE COMMISSION ADMINISTRATIVE LAW JUDGE'S HEARING REPORT


IL 524-0194

d	Hearing Date	
Case No. To7		
Petitioners	MARBUIS ENERLY V. NS	
Respondents		
Transcript Taken?		aken
Pleadings and Moti	,	
	RECEIVED	
	APR 3 2007	
	Illinois Commerce Commission RAIL SAFETY SECTION	
Exhibits Filed	EX" A. AERIAL PHOTO.	<u>_</u>
Remarks	B. ROADWAY ECHEMATIC W/ CROSSING.	
	C. PUTNAM WUNTY LTIL. SUPPORT	
	D. RESOLUTION FOR ROAD CONTRACTS. TO	പ്പം
	E. TOPOGRAPHIC CHART	
	I. ESK NOAD TRAFFIC INFO	
	J. ALUDENT HISTORY ESK ROAD	
	C. RR CROSSING DESIGN	
	H. HS GRADE CROSSNE SYSTEM	
	H. NS GRADE CROSSAUG SYSTEM F. CROSSING SCHEMATIC W/ ORANAGE DESIGNATION TRACK SYSTEM	6N
	Send Notice	
	Administrative Law Judge	5

(Administrative Law Judge: No hearing is completed until you have filled out this form in full)

DOCKETED

ILL C. C. DOCKET NO. TOT-0015



RAILROAD CROSSING LOCATION MAP




Illinois Valley Surveying and Consultants, Inc.

Land Surveying – Engineering

401 Court Street Hennepin, Illinois 61327 / P.O. Box 302

Phone: (815) 925-7511 – Fax: (815) 925-7580





Putnam County Highway

Mailing Address 6203 Illinois Highway 26 Hennepin, IL 61327

Office Address 552 State Route 26 Lacon, IL 61540

George P. Meister County Engineer Phone: (309) 246-6401 Fax: (309) 246-3446

March 20, 2007

Mr. Dean W. Jackson Illinois Commerce Commission Chief Administrative Law Judge 6th Floor 527 East Capitol Avenue Springfield, IL 62701

3092463446

RE: Notice of Hearing T07-0015

Dear Mr. Jackson:

Thank you for the Notice of Hearing on the above project, petition for an Order authorizing the construction of a new grade rail crossing of ESK Road (875E) in Hennepin Township, Putnam County, Illinois.

I have no objection to this work.

Sincerely,

Deorge P. Mister George P. Meister

County Engineer

GPM:cs

OFFICIAL FILE

ILL. C. C. DOCKET NO	707-0015
Letetiones Exhibit N	o
Witness	
Date 4/3/07 Reported	· CB

FFICIAL FILE

		ILL. C. C. DOCKET NO
STATE OF ILLINOIS)		Peletine Extribit No. D
)	SS.	Witness
COUNTY OF PUTNAM)		Date 4/3/12 Reporter CB
		, , , , , , , , , , , , , , , , , , , ,

RESOLUTION APPROVING AND AUTHORIZING CERTAIN ROAD PERMITS

WHEREAS, Putnam County has issued a permit to Marquis Energy LLC ("Marquis") to build an ethanol production plant north of the existing Mittal Steel plant; and

WHEREAS, the proposed ethanol production plant ("Plant") would provide employment and otherwise provide substantial economic benefits to the Township of Hennepin and Putnam County; and

WHEREAS, the Township Board of Hennepin Township in Putnam County wishes to provide all reasonable accommodations to Marquis to insure the construction of the Plant; and

WHEREAS, Marquis has asked Hennepin Township to provide, or assist in obtaining, certain permits to facilitate transportation to and from the Plant; and

WHEREAS, the Township Board of Hennepin Township wishes to provide, or assist Marquis in obtaining, the permits it is seeking for transportation to and from the Plant.

NOW, THEREFORE, BE IT RESOLVED by the Township of Hennepin, County of Putnam, a body politic and corporate of the State of Illinois, acting by and through its Township Board in regular meeting assembled, as follows:


- 1. The Township Highway Commissioner is directed to issue a permit to Marquis allowing a 200-foot wide roadway entrance from the west side of ESK Road to the Plant's east entrance to facilitate simultaneous ingress and egress of semi-trailer trucks to the Plant. The permit shall require the entrance to be of standard design, constructed of concrete with a normal turning radius. Marquis shall be required to provide all necessary labor and materials to install the roadway entrance and shall provide culverts/tubes as required to provide adequate drainage.
- 2. The Township Highway Commissioner is directed to issue a permit allowing Marquis to construct, use, operate, maintain, renew and remove a railroad grade crossing over ESK Road approximately 200 feet south of the north line of Section Two in Hennepin Township.


Exh. 6.7 D'

The permit shall require the grade crossing to be of standard design, and Marquis shall provide all necessary labor and materials to install the grade crossing and shall provide any necessary signage. The Township Highway Commissioner is further directed to assist Marquis in obtaining such other permits or governmental permissions as may be required for the construction and use of the grade crossing.


PASSED, APPROVED and ADOPTED this _/2 day of April, 2006.

Hennepin Township Clerk





TX Nigit F





"The Only Grade Crossing Manufacturer With The Full Product Line"


Norfolk Southern Standard Heavy Duty Road Crossing

OMNI's Embedded Concrete-Rubber (ECR) grade crossing system is the latest generation of OMNI's patented single-component, concrete-rubber design. ECR is designed with the rubber flange seal molded into the face of the concrete panels.


ECR is the fastest and easiest concrete crossing system to install because of its unique integrated concrete-rubber design.

As with all concrete systems, a well constructed foundation and track structure will ensure optimum life and performance. ECR is suitable for most traffic conditions.

For more information, view OMNI Products, Inc on the web at www.omnirail.com or



Embedded Concrete-Rubber (ECR) Cross-Section Illustration



Embedded Concrete-Rubber (ECR) Specifications

Panel Lengths: 8 feet 1 1/2 inches

Panel Heights: 7 1/8" or 7 7/8"

Tie Spacing: 19 1/2 inches

Gauge Panel Width: 51 inches

Field Panel Widths: 27 inches (10-foot tie)

Concrete:

Compressive Strength: 6000 p.s.i. Min.

Percentage of Entrained Air: 6.0 percent ± 1% Max. Water/Cement Ratio: 0.44 % (by weight)

Rebar:

ASTM A615 or A706 Gr.60 (Tied) ASTM A706 Gr.60 (Welded)

Rubber:

Type: Virgin SBR Tensile: 2,000 p.s.i.


Hardness: 65 ± 5 Durometer Shore A

OFFICIAL FILM

www.omnirail.com

RELICE OF DOORET HOS INTERNATIONAL HER

Exhibit H



Embedded Concrete-Rubber Installation Instructions

Track Preparation

- A. The track structure should be constructed per the surface data sheet.
- B. For best results, use new ballast, ties, and rail.
- C. Ties should be of good quality and in the same plane. Ties that are twisted or not set flat must be adzed or replaced.
- D. Ties must be placed center-to-center (c-c) as follows:

Panel Length

Timber Tie


8' 1 ½ "

19 ½ " c-c


- E. Rails should be welded. Grind welds smooth to avoid interfering with panels.
- F. Make certain that track gauge is 56 1/2".
- G. Sweep the ties and rail to remove ballast and debris which may interfere with seating of the panels.

Installation Steps


- 1. If ordered, gauge abrasion pads should be centered on the ties, field abrasion pads should be placed even with the outer edge of the ties. For timber ties, fasten the abrasion pads to the ties with the nails provided with the order.
- 2. Lubricate the underside of the rubber flangeway and the top of the adjoining rail with soapy water or pipe slick.
- 3. Install the first gauge panel, starting at the center of the crossing. Make sure the ends of the panels are centered on ties. Install the gauge panel by tipping the panel enough to place a flangeway beneath the rail head. Slowly lower panel until the opposing flangeway rests on the rail head.
- 4. Pull the panel towards the installed side. Then, force the opposing flangeway beneath the rail head with the use of a spike maul or lining bar. Do not hit the concrete panel.
- 5. Install the remaining gauge panels.
- 6. Begin installing field panels at the center of the crossing. Place the rubber nose of the panels against the rail. Make sure that the panel ends are centered on ties.
- 7. Install the remaining field panels.
- 8. For lagged installation, predrill the wood ties with a 1/2" drill bit and install 3/4" timber screws using a Torx bit and air impact wrench. Apply pressure to hold the field panels tight against the rail while drilling and fastening.
- 9. If ordered, install end-restraints. Do not span the gap of gauge panel frame.
- For welded installation, tack weld the gauge panels with four 3-inch skip welds and the field panels with three 3-inch skip welds.



Step 3: Gauge panel installation.




Step 4: Force rubber flange under rail using lining bar.



Step 7: Place field panel tight against rail.

W

Wineis Department of Transportation




All rights reserved. Use subject to License/Copyright Illinois Department of Transportation 2300 S. Dirksen Pky Springfield, IL 62764

OFFICIAL FILE

ILL. C. C. DOCKET NO.	707-0015
Petelone Exhibit	_
Witness	
Date 4/3/07 Repor	tor CB

Exhibit I





All rights reserved. Use subject to License/Copyright Illinois Department of Transportation 2300 S. Dirksen Pky Springfield, IL 62764

Putnam County Sheriff's Department

Accident Reports 2004 - 2006

County Road 875E... now known as ESK Rd.

<u>Date</u>	Sheriff's Dept. Report #	<u>Location</u>	<u>Details</u>
2004 11/18/2004		3/4 mi. North of Rt.71	Car vs. Deer
2005 No Reports			
2006 10/30/2006	PC06-158C	300' North of Rt. 71	Car vs. Deer

OFF	ici	ΔΙ	FA	LE
155				_

ILL. C. C. DOCKET NO	T07-0015
	it No.
Witness	uf.
Date 4/3/02 Rep	orter

Exhibit J